

## Stripping box



### Description:

The stripping box is an electrically-powered machine for the stripping of electrical or optical cables up to a maximum external diameter of 4.2 mm.

### Special features:

- Easy to adjust.
- User-friendly operation.
- Stripping of different types of cable without the need to change the cutting blade.
- Possibility to partially or completely strip the insulation from the cable.
- Step-switch for manual operation.
- Low space requirement.
- Only requires 220 V or 110 V mains power.
- Almost maintenance-free.
- Clean cut through cutting all around the insulation.
- Stepless adjustment of the stripping cross-section and stripping length.

**Specifications:**

<b>Stripping length:</b>	1.5 to 10 mm
<b>Stripping range:</b>	Stranded wire = 0.05 to 2.5 mm <sup>2</sup> / AWG 30 to 14 Solid wire = 0.25 to 2.5 mm <sup>2</sup> / AWG 30 to 10
<b>Max. external cable diameter:</b>	4.2 mm (1.4 mm with FE0400-1100 clamping head)
<b>Min. stripping length:</b>	12.5 mm + stripping length
<b>Cable suitable for stripping:</b>	Teflon, PVC or other insulated cables Fibre-optic cables Tinsel conductors
<b>Nominal voltage:</b>	FE0400 = 220 V, 50 Hz FE0401 = 110 V, 60 Hz
<b>Rated current:</b>	FE0400 = 260 mA FE0401 = 0.44 A
<b>Current consumption:</b>	FE0400 = 60W FE0401 = 60W
<b>Connection cable:</b>	Length approx. 1.8 m with moulded-on plug FE0400 with safety plug acc. to DIN49441 FE0401 with North American plug acc. to UL/CSA
<b>Weight:</b>	6.7 kg
<b>Dimensions:</b>	340 x 150 x 170 mm
<b>Machine space requirement:</b>	Apart from mains power, the stripping box does not require a special setup. The low weight of the box means that it can be placed on any standard table or workbench.

Specifications apply to the standard version.

Other specifications are available on request.